


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04N 13/04, G02B 27/26	A1	(11) International Publication Number: WO 00/21305
		(43) International Publication Date: 13 April 2000 (13.04.00)
(21) International Application Number: PCT/KR99/00596 (22) International Filing Date: 30 September 1999 (30.09.99) (30) Priority Data: 1998/41451 1 October 1998 (01.10.98) KR (71)(72) Applicant and Inventor: LEE, Young-Hwa [KR/KR]; 586-21, Jayang-dong, Goangjin-ku, Seoul-shi 143-190 (KR). (74) Agent: PARK, Gilcem; #401, New Seoul Building, 828-8, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).		(81) Designated States: CA, CN, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: THREE-DIMENSIONAL IMAGE FLUOROSCOPY SYSTEM

(57) Abstract

In a three-dimensional image fluoroscopy system constructed by a three-dimensional image monitor (10) and three-dimensional image fluoroscopy glasses (14), the three-dimensional image fluoroscopy glasses (14) having a liquid crystal shutter (12) to see the three-dimensional image monitor (10) by fluoroscopy, the system comprises one polarized-light film set (16) only to an eye lens side in the liquid crystal shutter (12) of the three-dimensional image fluoroscopy glasses (14); and another polarized-light film (18) of a both-eyes common usage set to a fore face of the three-dimensional image monitor (10). Under such construction, incident light of an object not polarized in spite of an operation of the liquid crystal shutter (12) enters through the liquid crystal shutter (12) and the polarized-light film (16) of the eyes lens side, in a case of seeing by fluoroscopy objects except that displayed on the three-dimensional image monitor (10). Accordingly, there is not a flickering phenomenon regardless of the operation of the liquid crystal shutter (12), and there is an additional effect that right and left images on a screen of the three-dimensional image monitor (10) are not mixed each other, even though a user sees by fluoroscopy the three-dimensional image monitor (10) in an oblique posture in a state of wearing the three-dimensional image fluoroscopy glasses (14).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

THREE DIMENSIONAL IMAGE FLUOROSCOPY SYSTEM**BACKGROUND OF THE INVENTION****Field of the Invention**

5 The present invention relates to a three-dimensional image fluoroscopy system, and more particularly, to a three-dimensional image fluoroscopy system capable of preventing a flickering phenomenon when a user sees by fluoroscopy objects except that displayed on a three-dimensional
10 image monitor under a state of wearing three-dimensional image fluoroscopy glasses.

Discussion of Related Art

 In a general three-dimensional image fluoroscopy system shown in Fig. 1 as a typical example, a three-dimensional image
15 is displayed on a three-dimensional image monitor 1, and a user puts on three-dimensional image fluoroscopy glasses 5 provided with a liquid crystal shutter 4, to thereby see the three-dimensional image by fluoroscopy, wherein the liquid
20 crystal shutter 4 is disposed between fore and rear polarized-light films 2, 3 having a polarized angle of 90 degrees.

 Herewith, the liquid crystal shutter 4 is connected electrically so as to synchronize to an image signal of the three-dimensional image monitor 1. As well-known, right and
25 left eyes fluoroscopy images are displayed on the three-dimensional image monitor 1 at a speed of 60 frames per second, and right and left liquid crystal shutters 4 are turned on/off by an input of the signals synchronizing to the images of the three-dimensional image monitor 1, to thus enable to
30 see the three-dimensional images by fluoroscopy.

 In such constructed three-dimensional image fluoroscopy system, however, in case the user sees other objects by

SUBSTITUTE SHEET (RULE 26)

2

fluoroscopy instead of staring at images displayed on the three-dimensional image monitor 1 in a state of wearing the glasses 5, the user feels a serious flickering phenomenon caused by an operation of the liquid crystal shutter 4, therefore
5 feels a severe eye strain.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a three-dimensional image fluoroscopy system that substantially
10 obviate one or more of the limitations and disadvantages of the related art.

A primary object of the present invention is to provide a three-dimensional image fluoroscopy system, in which a polarized-light film of a fore face provided in a prior art
15 is removed from three-dimensional image fluoroscopy glasses, to thereby prevent a flickering phenomenon by incident light of an object not based on polarized-light in spite of an operation of a liquid crystal shutter, in a case of seeing by fluoroscopy objects except that displayed on the three-dimensional image
20 monitor, meantime to enable to appreciate three-dimensional images in a case of seeing images of the three-dimensional image monitor by fluoroscopy.

To achieve these and other advantages, and in accordance with the purpose of the present invention as embodied and broadly
25 described, in a three-dimensional image fluoroscopy system constructed by a three-dimensional image monitor and three-dimensional image fluoroscopy glasses, the three-dimensional image fluoroscopy glasses having a liquid crystal shutter to see the three-dimensional image monitor
30 by fluoroscopy, the system comprises one polarized-light film set only to an eye lens side in the liquid crystal shutter of the three-dimensional image fluoroscopy glasses; and another

SUBSTITUTE SHEET (RULE 26)

3

polarized-light film of a both-eyes common usage set to a fore face of the three-dimensional image monitor.

Further, in a three-dimensional image fluoroscopy system composed of a three-dimensional image monitor and
5 three-dimensional image fluoroscopy glasses, the three-dimensional image fluoroscopy glasses having a liquid crystal shutter to see the three-dimensional image monitor by fluoroscopy, the system includes a polarized-light film set to an eye lens side in the liquid crystal shutter positioned
10 between the polarized-light film and a phase difference film; a phase difference film set, being directed to the three-dimensional image monitor side, onto the liquid crystal shutter; and a circularly polarized-light film of a both-eyes common usage adhering to a fore face of the three-dimensional
15 image monitor.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

20

BRIEF DESCRIPTION OF THE ATTACHED DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate
25 embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

Fig. 1 represents a schematic view showing a conventional
30 three-dimensional image fluoroscopy system;

Fig. 2 indicates a schematic view providing a three-dimensional image fluoroscopy system based on a first

SUBSTITUTE SHEET (RULE 26)

4

embodiment in accordance with the present invention; and

Fig. 3 sets forth a schematic view depicting a three-dimensional image fluoroscopy system based on a second embodiment of the present invention.

5

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

10 As shown in Fig. 2, a three-dimensional image fluoroscopy system based on a first embodiment of the invention is constructed by a three-dimensional image monitor 10 and three-dimensional image fluoroscopy glasses 14, the three-dimensional image fluoroscopy glasses having a liquid crystal shutter 12 to see
15 by fluoroscopy the three-dimensional image monitor. In this construction, the three-dimensional image fluoroscopy system is composed of one polarized-light film 16 set only to an eye lens side in the liquid crystal shutter 12 of the three-dimensional image fluoroscopy glasses 14; and another
20 polarized-light film 18 of a both-eyes common usage set to a fore face of the three-dimensional image monitor 10.

Operations of such constructed system are described as follows.

A user puts on the three-dimensional image fluoroscopy
25 glasses 14, and he can feel three-dimensional images by such procedures that an operation of a polarization light is performed through the polarized-light film 18 of the both-eyes common usage adhering onto a fore face of the three-dimensional image monitor 10, that it again passes through the liquid crystal
30 shutter 12, and that an operation of the polarization light is also executed through the polarized-light film 16 of the eye lens side.

SUBSTITUTE SHEET (RULE 26)

5

Meanwhile, in case the user sees other objects instead of them on the three-dimensional image monitor 10 under a state of wearing the three-dimensional image fluoroscopy glasses 14, it is available to normally see them without a flickering phenomenon, regardless of an operation of the liquid crystal shutter 12, since incident light of other objects not polarized enters through the liquid crystal shutter 12 and the polarized-light film 16 of the eye lens side.

As shown in Fig. 3, a three-dimensional image fluoroscopy system based on a second embodiment of the present invention is constructed by a three-dimensional image monitor 10 and three-dimensional image fluoroscopy glasses 14, the three-dimensional image fluoroscopy glasses having a liquid crystal shutter 12 to see by fluoroscopy the three-dimensional image monitor. In this construction, the three-dimensional image fluoroscopy system includes a polarized-light film 16 set to an eye lens side of the liquid crystal shutter 12 positioned between the polarized-light film 16 and a phase difference film 20; a phase difference film 20 set, being directed to the three-dimensional image monitor side, onto the liquid crystal shutter 12; and a circularly polarized-light film 30 adhering to a fore face of the three-dimensional image monitor 10.

The penetration light from the three-dimensional image monitor 10 becomes a circularly polarized light state through the circularly polarized-light film 18, therefore, not only right and left images on a screen of the three-dimensional image monitor 10 do not become composite each other, but also a peripherally flickering phenomenon does not occur, even though a user sees by fluoroscopy the three-dimensional image monitor 10 in an oblique posture in a state of wearing the three-dimensional image fluoroscopy glasses 14.

As afore-mentioned, in accordance with the inventive

SUBSTITUTE SHEET (RULE 26)

three-dimensional image fluoroscopy system, a polarized-light film is set only to an eye lens, or a phase difference film adheres, being directed to a three-dimensional image monitor side, to the liquid crystal shutter. Further, a polarized-light film based on a both-eyes common usage, or a circularly polarized-light film adheres to a fore face of a three-dimensional image monitor. Under such construction, incident light of an object not polarized in spite of an operation of a liquid crystal shutter enters through the liquid crystal shutter and the polarized-light film of the eye lens side, in a case of seeing by fluoroscopy objects except that displayed on the three-dimensional image monitor, accordingly, there is not a flickering phenomenon regardless of the operation of the liquid crystal shutter. In addition, there is an effect that right and left images on a screen of the three-dimensional image monitor are not mixed each other, even though a user sees by fluoroscopy the three-dimensional image monitor in an oblique posture in a state of wearing the three-dimensional image fluoroscopy glasses.

It will be apparent to those skilled in the art that various modifications and variations can be made in the three-dimensional image fluoroscopy system of the present invention without deviating from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

SUBSTITUTE SHEET (RULE 26)

What is claimed is:

1. A three-dimensional image fluoroscopy system constructed by a three-dimensional image monitor and
5 three-dimensional image fluoroscopy glasses, said three-dimensional image fluoroscopy glasses having a liquid crystal shutter to see the three-dimensional image monitor by fluoroscopy, said system comprising:

one polarized-light film set only to an eye lens side
10 in the liquid crystal shutter of the three-dimensional image fluoroscopy glasses; and

another polarized-light film of a both-eyes common usage set to a fore face of the three-dimensional image monitor.

15 2. A three-dimensional image fluoroscopy system composed of a three-dimensional image monitor and three-dimensional image fluoroscopy glasses, said three-dimensional image fluoroscopy glasses having a liquid crystal shutter to see the three-dimensional image monitor by fluoroscopy, said system
20 comprising:

a polarized-light film set to an eye lens side in the liquid crystal shutter positioned between the polarized-light film and a phase difference film;

a phase difference film set, being directed to the
25 three-dimensional image monitor side, onto the liquid crystal shutter; and

a circularly polarized-light film of a both-eyes common usage adhering to a fore face of the three-dimensional image monitor.

30

3. Three-dimensional image fluoroscopy glasses having a liquid crystal shutter to see by fluoroscopy a

SUBSTITUTE SHEET (RULE 26)

three-dimensional image monitor in a three-dimensional image fluoroscopy system, said glasses comprising:

a polarized-light film set to an eye lens side in the liquid crystal shutter positioned between the polarized-light


film and a phase difference film; and

a phase difference film set, being directed to the three-dimensional image monitor side, onto the liquid crystal shutter.

SUBSTITUTE SHEET (RULE 26)


1/3

FIG. 1




2/3

FIG. 2



3/3

FIG. 3



INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR 99/00596

A. CLASSIFICATION OF SUBJECT MATTER

IPC⁷: H 04 N 13/04; G 02 B 27/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷: H 04 N 13/00, 13/04, 15/00; G 02 B 27/22, 27/26

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97/43681 A1 (FARIS BT AC.), 20 November 1997 (20.11.97), fig.6A,7; claims 4,5.	1-3
A	JP 09-138384 A (SANYO ELECTRIC), Patent Abstracts of Japan, Vol.199, No.709, 30 September 1997 (30.09.97), Database PAJ in EPOQUE.	1-3
A	US 4431265 A (BENTON), 14 February 1984 (14.02.84), fig.4; claim 1.	1-3

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

„A“ document defining the general state of the art which is not considered to be of particular relevance

„E“ earlier application or patent but published on or after the international filing date

„L“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

„O“ document referring to an oral disclosure, use, exhibition or other means

„P“ document published prior to the international filing date but later than the priority date claimed

„T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

„X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

„Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

„&“ document member of the same patent family

Date of the actual completion of the international search

19 January 2000 (19.01.00)

Date of mailing of the international search report

23 February 2000 (23.02.00)

Name and mailing address of the ISA/AT
Austrian Patent Office
Kohlmarkt 8-10; A-1014 Vienna
Facsimile No. 1/53424/200

Authorized officer

Fussy

Telephone No. 1/53424/328

Form PCT/ISA/210 (second sheet) (July 1998)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.
PCT/KR 99/00596

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	A1	9743681	20-11-1997	AU	A1 31229/97	05-12-1997
				US	A 5821989	13-10-1998
				US	A 5327285	05-07-1994
				US	A 5844717	01-12-1998
				US	A 6002518	14-12-1999
				US	A 5502481	26-03-1996
				US	A 6011581	04-01-2000
				US	A 5537144	16-07-1996
				US	A 5828427	27-10-1998
				US	A 5886816	23-03-1999
				US	A 5165013	17-11-1992
				US	A 5553203	03-09-1996
				AU	A1 23968/95	16-11-1995
				EP	A1 760965	12-03-1997
				EP	A4 760965	11-06-1997
				JP	T2 9512383	09-12-1997
				WO	A1 9529427	02-11-1995
				US	A 5680233	21-10-1997
				US	A 5801793	01-09-1998
				AU	A1 41290/96	06-05-1996
				WO	A1 9612210	25-04-1996
				AU	A1 41597/96	06-06-1996
				WO	A1 9615632	23-05-1996
				AU	A1 11510/97	19-06-1997
				WO	A1 9720250	05-06-1997
				AU	A1 22106/97	01-10-1997
				WO	A1 9734184	18-09-1997
				AU	A1 49017/96	07-08-1996
				WO	A1 9622660	25-07-1996
JP	A2	9138384	27-05-1997	none		
US	A	4431265	14-02-1984	none		